

	PRODUCT INFORMATION	Mod. R&S.	Rev.	Last updated	Page
		05	03	12/2015	1 of 1

STRIPFLOCK®

Description Plotter cut flock heat seal material with polyester backing.

Average film thickness : **500 micron**

Usage informations Due to the many different base materials available on the market, the following instructions are given as a guideline only :
Plotter settings (eg. with ROLAND GX-24)
 Blade: **new for high thickness materials**
 Minimum cutting pressure: **100 gf**
Transfer setup
 Temperature: **160 °C (320°F)**
 Time: **15 seconds**
 Pressure: **medium (3÷4 bar)**

Procedure
 Mirror cut the material. We recommend using high thickness blades.
 Weed the exceeding material
 Place the material on the garment with its polyester backing
 Heat apply
 Remove the support cold

Certifications The product is REACH compliant.

Suitable textiles Cotton, polyester and blends of these materials
 (not suited for treated and dye sublimation fabrics)

Washing instructions Wait **24h** after the heat transfer
60°C
 Do not use bleach or other aggressive chemical agents.
 Dry clean: **no**
 Tumble dry: **yes**



Siser s.r.l.

Viale della Tecnica n° 18
 36100 Vicenza - Italy
 Tel. +39 0444.287960
 Fax +39 0444.287959
 info@siser.it - www.siser.it

N.B. All information given in this sheet are based on our experience.
 We always recommend performing a test before starting standard production.
 For best results we recommend to store the product away from direct sunlight.

The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).
 This document can be subject to variations. Updated versions are available on our website www.siser.it.
 For further information, please contact our Sales Office.
 Thank you.