

MODA GLITTER 2

Description	PU plotter cut heat seal material with high thickness glitters and adhesive polyester
	backing.

Average film thickness before transfer: 350 micron

 Usage informations
 Due to the many different base materials available on the market, the following instructions are given as a guideline only :

 Plotter settings (eg. with SUMMACUT D60 – ROLAND GX24)

 Blade: new for high thickness materials

 Minimum cutting pressure: 120 gf

 Transfer setup

 Temperature: 160 °C (320°F)

 Time: 15 seconds

 Pressure: medium (3÷4 bar)

 N.B.: the material is not suited for creation of small details. Its special structure tends to wear out the blade.

 Mirror cut the material

Weed the exceeding material Place the material on the garment with its polyester backing Heat apply Remove the support either cold or warm

Certifications The product is REACH approved

Suitable textiles	Cotton, polyester and blends of these materials (not suited for treated and dye sublimation fabrics)
Washing instructions	Wait 24h after the heat transfer 40°C - inside out
	Do not use bleach or other aggressive chemical agents. Dry clean: no
	Tumble dry: not recommended
Venerated Venera	 N.B. All information given in this sheet are based on our experience. We always recommend performing a test before starting standard production. For best results we recommend to store the product away from direct sunlight.
Viale della Tecnica nº 18 36100 Vicenza - Italy Tel. +39 0444.287960 Fax +39 0444.287959 info@siser.it - www.siser.it	The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation in 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance). This document can be subject to variations. Updated versions are available on our website www.siser.it. For further information, please contact our Sales Office. Thank you.